

Miracord™ 50 Turntable

Smooth vinyl precision.

ELAC's Miracord 50 Turntable is designed to deliver exceptional vinyl transcription, inspired by the iconic Miracord name from the Golden Age of Stereo, when turntables reigned supreme. The Miracord 50 is carefully engineered with a belt-drive motor and aluminum die-cast platter. A precision static-balanced, straight-tube tonearm with removable headshell features a factory-mounted MM phono cartridge. Designed with convenience in mind, the Miracord 50 is equipped with a built-in phono preamplifier, allowing you to add this turntable to any music system.



Miracord 50 Turntable

The warmth of analog sound.

The resurgence of vinyl has created a groundswell of enthusiasm among audiophiles and even music enthusiasts who have never before enjoyed the thrill of spinning an LP! The Miracord 50 is the perfect choice for those building a new LP collection, or for rediscovering the magic of an existing record library.

MIRACORD 50 TURNTABLE FEATURES

Anti-resonant Chassis

Superior isolation is achieved with a chassis designed to minimize the sonic effects of vibration and feedback. A low-noise DC servo motor drives a die-cast, high-inertia aluminum platter with special record mat via a rubber belt, resulting in stable speed and minimal wow and flutter.

Precision Tonearm and Cartridge

The tonearm is a static-balance, straight-tube design with precision bearings, built-in anti-skate adjustment and removable bayonet-style headshell. A premounted

moving-magnet cartridge takes all the guesswork out of setup and assures proper vertical tracking angle, tracking weight and azimuth adjustment right out of the box.

Built-in Phono Equalizer Amplifier

Unlike most turntables, the Miracord 50 comes complete with a built-in phono preamp for correct RIAA equalization. That means you can add LP playback without having to add a costly phono stage to line-level preamps or digital-only systems. Just plug it in, put on a record and enjoy rich LP sound!

Contemporary or Traditional Finish

Styled to complement any interior, the Miracord 50 is available with a silver chassis and gloss-black plinth, or black chassis with walnut veneer plinth. A hinged, tinted dustcover is included.



MIRACORD 50 TURNTABLE SPECIFICATIONS

TURNTABLE SECTION

- | | |
|----------------------------|--|
| • Drive System | Belt drive |
| • Motor | DC motor |
| • Selectable Speeds | 33⅓ and 45 rpm |
| • Motor Servo | Speed rotation and servo system |
| • Rotation Speed Variation | +/-1% |
| • Wow and Flutter | 0.1% |
| • Signal-to-Noise Ratio | -67 dB or higher (A-weighted)
-60 dB or higher (unweighted) |
| • Platter | Aluminum die-cast |
| • Platter Diameter | 12.0 in / 300 mm |

ONEARM SECTION

- | | |
|---------------------------|--------------------------------|
| • Type | Aluminum tube, static-balanced |
| • Effective Arm Length | 8.8 in / 223.6 mm |
| • Stylus Pressure Range | 0 to 4.0 g |
| • Cartridge Weight Range | 3.5 to 6.0 g |
| • Effective Arm Mass | 27.4 g |
| • Overhang | 18.6 mm |
| • Offset Angle | 25 degrees |
| • Anti-Skating Adjustment | Supported |
| • Main Bearing | Stainless steel |

CONNECTOR

RCA pin jack including RCA cable accessories

VOLTAGE

100 to 240 V AC / 50 to 60 Hz

POWER CONSUMPTION

1.5 W (less than 0.5 W at standby)

DIMENSIONS (WIDTH)

16.5 in / 420 mm

WEIGHT

8.6 lb / 3.9 kg (approx.)

CARTRIDGE SECTION

- | | |
|----------------------------|-----------------------------------|
| • Type | Audio-Technica AT90 moving magnet |
| • Stylus Construction | Bonded diamond |
| • Mount | Half-inch |
| • Frequency Response | 20 Hz to 20 kHz |
| • Channel Separation | >18 dB |
| • Channel Balance | 2.5 dB |
| • Vertical Tracking Angle | 20 degrees |
| • Supported Load Impedance | 47 kΩ |

PHONO EQUALIZER AMPLIFIER

- | | |
|--------------------|---|
| • Type | Moving magnet (MM) |
| • Phono Output | 2.5 mV (1 kHz, 3.54 cm/sec) |
| • Line Output | 140 mV (-17 dBV) |
| • Phono/Line | Switchable |
| • Stylus Pressure | 3.5 g +/-0.5 g |
| • Cartridge Weight | 5.0 g +/-0.5 g |
| • Headshell Weight | 11.0 g (including screws, nuts and wires) |



ELAC Miracord™ Series

ELAC.com

©2018 ELAC Americas, Inc. All rights reserved. Specifications and design subject to change without notice.