

[Home](#)[Products](#)[News](#)[Reviews](#)[Support](#)[Sales](#)[AM-777](#) | [Features](#) | [Reviews](#) | [FAQ](#) | [Gallery](#) | [Specifications](#) | [Manual](#)

AM-777 Specifications

Inputs:

- 4 x RCA
- 1 x XLR Bal. shared with 1 RCA
- 1 x USB

Volume Control:

- -71dB – 0dB in 1dB steps + Mute

Input Sensitivity (IHF 2.83V Out)/Impedance:

- < 0.05V / > 20KOhm

Analogue Outputs:

- 1 x RCA; 1 x XLR per channel

Power Output IHF Dynamic Power:

- 60 watts per channel at 4 or 8 ohm (stereo mode)
- 70 watts per channel at 8 ohm (monoblock mode)
- 120 watts per channel at 2 or 4 ohm (monoblock mode)

FTC:

- 60 watts per channel at 4 or 8 ohm (stereo mode)
- 70 watts at 8 ohm (monoblock mode)
- 120 watts per channel at 2 or 4 ohm (monoblock mode)

Output impedance:

- 0.33 ohm, 20 - 20,000 Hz

Frequency Response (-1dB):

- 10Hz - 30kHz

Signal-to-noise ratio "A" weighted:

- >100 dB

Total Harmonic Dist. + Noise (THD+N):

- < 0.3%

Operational Modes:

- Pre-Main amplifier mode;
- Power amplifier mode
- Monoblock option;

Thermionic Electron Valves amplification stage:

- 6H1n-EV fitted
- ECC88, E88CC, 7308, Cca, 6DJ8, 6922,
- 6H23n-EV optional

Power Transformer:

- 380 VA Custom Torroid (Output Stage)
- 32 VA Custom EI Transformer (Valve Stage)

Power consumption:

- Standby: <1 W
- Power on: 25 W
- at rated output (4R): 250 W

Power Supply Capacitance:

- 44,000uF in total

Rated voltage:

- 100V/120V/230V~ AC 50Hz - 60Hz

Mains Fuse:

- 100V/120V: 4A slow blow; 230V: 2A slow blow

Colour:

- Silver or Black

Dimensions:

- 17.7 in W by 4.7 in H by 14.6 in D
- 45 cm W by 12 cm H by 37 cm D
- 57 cm W by 49 cm H by 25 cm D (shipped)

Weight:

- AM-777: 31 lbs / 14 kg
- Shipped: 40 lbs / 18 kg

Information and specifications are subject to change without notice.